



ALPHA DATA

# ADB3 Driver 1.1.2 for Linux Release Note

## Introduction

This release note accompanies the ADB3 Driver for Linux. The latest version of this driver can be found at:  
<ftp://ftp.alpha-data.com/pub/admxrcg3/linux>  
For support, send e-mail to [support@alpha-data.com](mailto:support@alpha-data.com)

## Operating systems supported

This release of the ADB3 Driver supports the following operating systems:

- GNU/Linux distribution with 2.6.x kernel

Due to the ever-changing nature of GNU/Linux, Alpha Data cannot guarantee that this driver can be successfully configured, built, installed and run on all Linux distributions past, present and future. Alpha Data makes best-efforts to ensure compatibility with all Linux distributions, but should a problem be encountered, please contact [support@alpha-data.com](mailto:support@alpha-data.com).

## Hardware supported

This release of the ADB3 Driver supports the following Alpha Data hardware:

- ADM-XRC-6TL
- ADM-XRC-6T1

## License Agreement

This release of software is licensed according to the terms of GNU Public License Version 2 (GPL V2). A copy of this license can be found in the file **gpl-2.0.txt** within this software package. Please contact Alpha Data if alternative licensing conditions are required.

Alpha Data reserves the right to use a different license agreement for future releases of this software.

## Installation instructions

This release of the driver is distributed in source code form as a tarball (.tar.gz file extension). Please refer to the README file inside the tarball for instructions on how to configure, build and install the driver.

## VPD write-protection mechanism

The VPD write-protection mechanism described in the ADM-XRC Gen 3 SDK User Guide is implemented as of release 1.1.0. To enable write-to-VPD, the kernel module parameter **EnableVpdWrite** must be nonzero. This value is set when the driver starts, so it can be changed only by unloading the driver and restarting the driver with a different value for **EnableVpdWrite**. If this parameter is not specified, the driver considers it to be zero (write-to-VPD disabled).

## Known issues

## Security considerations

As of release 1.1.0, the script **adb3.rc** that creates device nodes in **/dev** applies permissions 666 (previous version of the driver applied permissions 600). When a user-mode process attempts to open a device, the driver verifies that either (a) the user-mode process is opening the device in "read only" mode, or (b) the user owning the process is a system administrator. If neither are true, the driver rejects the attempt to open the device. In the case of (a), the driver restricts the user-mode process to using a subset of the device's functionality so that the device does not compromise system security.

## Partial udev support

In this release of the driver, a script **adb3.rc** is provided in order to start the driver. This creates device nodes in **/dev** rather than relying on **udev** rules. This will be corrected in a future release.

## Downgrading to an earlier version

When downgrading to an earlier version of the driver, remove all files named **/usr/lib/libadmxrc3.\***, (and **/usr/lib64/libadmxrc3.\*** if on a 64-bit bi-architecture machine), before executing the **make install** command as root. Otherwise, the shared libraries remaining from the later version of the driver will be preferred by the system as they have a higher version number.

When downgrading to a driver earlier than 1.1.0, delete any device nodes **/dev/admxrc3\*** before installing the earlier driver, as a safety precaution. This is recommended because a pre-1.1.0 ADB3 driver relies upon the device nodes being owned by root with permissions 600 in order to restrict access to privileged users.

## Fixed-local addressing DMA transfers

The flag **ADMXRC3\_DMA\_FIXEDLOCAL** currently has no effect for the ADM-XRC-6TL and ADM-XRC-6T1 when used with the DMA functions in the **ADMXRC3** API.

## Release history

### Release 1.1.2

Corrections:

1. Fixed a user-mode memory leak that can occur when the API functions **ADMXRC3\_LoadBitstreamA** and **ADMXRC3\_LoadBitstreamW** return a failure status code.
2. Fixed a bug in **ADMXRC3\_SetClockFrequency** where on failure, the wrong status code was returned.

### Release 1.1.0

Corrections:

1. Fixed a potential memory corruption issue on some architectures due to incorrect byte size calculation in device context structure.
2. Fixed a memory leak related to CFI Flash functionality when stopping and restarting the driver.
3. Fixed user VPD area (VPD space address range 0x100000-0x1FFFFFF) not being accessible on ADM-XRC-6TL and ADM-XRC-6T1.
4. Corrected error codes returned by several **ADMXRC3** API functions when invalid parameters are passed:
  1. Non-Locked DMA functions now return 'ADMXRC3\_INVALID\_BUFFER' if the 'pBuffer' and/or 'length' parameters are invalid.
  2. Locked DMA functions now return 'ADMXRC3\_INVALID\_BUFFER\_HANDLE' if the 'hBuffer' parameter is invalid.
  3. **ADMXRC3\_Unlock** now returns 'ADMXRC3\_INVALID\_BUFFER\_HANDLE' if the 'hBuffer' parameter is invalid.
5. Fixed 'ADMXRC3\_Unconfigure' failing with 'ADMXRC3\_NOT\_OWNER' even when the target FPGA has no owner.
6. Fixed the **ADMXRC3** DMA functions not properly co-validating the 'local' and 'length' parameters.

7. Fixed the ADMXRC3 Locked DMA functions not properly co-validating the 'offset' and 'length' parameters.
8. Fixed the ADMXRC3 nonblocking DMA functions incorrectly returning 'ADMXRC3\_SUCCESS' instead of 'ADMXRC3\_PENDING' when 'length' is zero and all other parameters are OK.
9. Fixed the ADMXRC3 non-Locked DMA functions not properly co-validating the 'pBuffer' and 'length' parameters.
10. Fixed certain ADMXRC3 API functions not trapping NULL pointers being passed, typically resulting in an application crash.
11. Fixed a bug in driver parameter handling so that driver parameters are now correctly applied and have correct default values.
12. Implemented VPD write-protection mechanism (now protected by default).
13. Added workaround for 4k crossing issue in ADB3 Bridge rev 0x01 and earlier. Workaround is not applied for rev 0x02 or later.

Enhancements:

14. Added support for ADM-XRC-6T1.
15. Added API function ADMXRC3\_OpenEx, which allows an unprivileged process to open a device in "read only" mode and use a subset of the ADMXRC3 API functions.
16. Added API functions ADMXRC3\_StartNotificationWait and ADMXRC3\_FinishNotificationWait, which allow Linux applications to wait for events (since there is no Linux equivalent of ADMXRC3\_RegisterWin32Event).
17. Added API function ADMXRC3\_GetCardInfoEx (with structure ADMXRC3\_CARD\_INFOEX), which returns a superset of data supplied by ADMXRC3\_GetCardInfoEx.
18. Added diagnostic API functions ADMXRC3\_GetSensorInfo and ADMXRC3\_ReadSensor, with associated types and structures. These functions allow applications to monitor the health of a Gen 3 reconfigurable computing card.

## Release 1.0.0

This is the first release of the ADB3 Driver for Linux.

Page Intentionally left blank.